



*Specialising in Anti-Slip floor Treatments  
Increasing Safety by Reducing Risk*

**On Site Pendulum Test and application of anti slip treatment.**



Wessex Pendulum

The Pendulum BS 7976 is well established as a world leader in its field and the only **UK court law testing method**.

Today it is the industry standard and still the only recognised test by the HSE for a vast array of surface testing applications.

**HSE Guidelines:**

0 - 24 High Risk Slip potential

25 - 35 Medium Risk for Slip Potential

36+ Low Risk for slip potential

**What's involved in the test:** (Approximately 1sq mtr is required for testing)

Test the floor wet as found in two directions - Record 8 readings.

Test the floor wet after cleaning in two directions - Record 8 readings.

If need be apply anti slip treatment in increments of 10 minutes.

Retest and reapply anti slip treatment until 36+ is recorded on the Pendulum\*\*.

Issue a full report via email of all the readings.

It would also provide a paperwork trail to endorse the Companies commitment to 'Due Diligence'

**\*£350.00 + vat.**

Payment due on / before the day of the test.

Please let us know if you need an invoice before in order to raise a cheque

\*\* 36+ is the benchmark set by the HSE - However certain anomalies with in the aesthetics of a floor can prevent the pendulum being able to read it.

\*Price start from £350 depending on location